

## AT-AWG-1102 performance specifications

Document name: AT-AWG-1102

Revision: C

Date:31/07/2019

Unless otherwise noted the following conditions are used:

- Ambient temperature between 0°C and 50°C
- Warm up time > 20 minutes
- Humidity: 5% to 80% RH (non-condensating) at ≤ 30 (0°C to 40°C), 50% max RH (non-condensing) at 40degree C

Typical values cover the expected performance over ambient temperature ranges of 23°C ± 5°C with a 95% confidence level and humidity < 50%.

Specifications	Limits	
Channel operating mode	Arbitrary	DDS
Number of Channels	2	
Waveforms	Sine, Cosine, Triangle, Rectangle, Sawtooth, Ramp, Pulse, Sinc, Exponential, Sweep, DC, Noise, From File, Arbitrary	
Sine Waves		
Frequency Range	2 μHz to 125 MHz	3.7 MHz to 110 MHz (@ Max sample rate)
Amplitude Flatness (1 Vp-p), typical		
DC to 125 MHz	< ± 0.1 dB	
DC to 110 MHz		< ± 0.1 dB
Harmonics Distortion (1 Vp-p), typical		
≤ 1 MHz	< -66dBc	< -66dBc
1 MHz to 5 MHz to	< -63dBc	< -63dBc
5 MHz to 10 MHz	< -59dBc	< -59dBc
10 MHz to 25 MHz	< -53dBc	< -53dBc
25 MHz to 75 MHz	< -38dBc	< -38dBc
75 MHz to 125 MHz	< -28dBc	
75 MHz to 110 MHz		< -31dBc
Non Harmonic Distortion (1 Vp-p, Frequency range DC to 200 MHz), typical		
≤ 1 MHz	< -71dBc	< -63dBc
1 MHz to 5 MHz to	< -71dBc	< -63dBc
5 MHz to 10 MHz	< -71dBc	< -63dBc
10 MHz to 25 MHz	< -66dBc	< -63dBc
25 MHz to 75 MHz	< -53dBc	< -61dBc
75 MHz to 125 MHz	< -47dBc	
75 MHz to 100 MHz		< -61dBc
100 MHz to 110MHz		< -30dBc
THD (100 KHz, 1 Vp-p), typical	< 0.15%	
Phase noise (20 MHz, 1 Vp-p), typical		
10 KHz offset	-130 dBc/Hz	
100 KHz offset	-132 dBc/Hz	
1 MHz offset	-133 dBc/Hz	
Analog Bandwidth	125 MHz	110 MHz

<b>Arbitrary Mode Specifications</b>	
<b>Square Wave, Pulse</b> (1 V <sub>p-p</sub> )	
Frequency Range	2 µHz to 62.5 MHz
Duty Cycle Range	1% to 99%
Rise/Fall Time, typical	< 3.5 ns
Overshoot, typical	< 5.5%
Random jitter (rms), typical	< 20 ps
<b>Triangle</b>	
Frequency Range	2 µHz to 31.25 MHz
Start Phase Range	0 to 360°
<b>Ramp</b>	
Frequency Range	2 µHz to 31.25 MHz
<b>Sinc (Sine(x)/x)</b>	
Frequency Range	2 µHz to 15.5 MHz
Minimum Lobe Width	8 ns
<b>Amplitude Modulation</b>	
Modulation type	Arbitrary AM, ASK
Carrier waveform	All, From File, Arbitrary
Modulating waveforms	All, From File, Arbitrary
Modulating source	Internal
Modulating waveform sample clock (@ Max. sampling rate)	0.46 S/s to 125 MS/s
Memory size	2047 entries
<b>Waveform sequencing</b>	
Waveforms	All, From File, Arbitrary
Waveform repetitions	1 to (2 <sup>33</sup> - 1)
Start source	Software, Internal, External
No. of waveforms	1 to 511
<b>General</b>	
Sample rate real time	4 S/s to 250 MS/s
Vertical res.	16 Bit
Waveform memory	2 MSamples / Ch.
Min. waveform length	8 points
Waveform resolution	2 points
Noise bandwidth (-3 dB gaussian noise), typical	100 MHz
Run Modes	Single, Continuous, Stepped, Burst
<b>DDS Mode Specifications</b>	
<b>Phase/Frequency Modulation</b>	
Modulation type	Arbitrary FM/PM, FSK, PSK
Carrier waveform	All, From File, Arbitrary
Modulating waveforms	All, From File, Arbitrary
Modulating source	Internal
Carrier frequency (@ Max. sample rate)	
Sine wave	3.7mHz to 110 MHz
Square	3.7mHz to 62.5 MHz
Triangle	3.7mHz to 31.25 MHz
Ramp	3.7mHz to 31.25 MHz
Modulating waveform sample clock (@ Max. sample rate)	From 119.2S/s to 125 MS/s (per sample programmable)
Memory size	511 entries
Frequency resolution	0.0019 Hz (FSK), 2.15E-5° (PSK) @ 125 MS/s sample rate 0.0037 Hz (FSK), 4.30E-5° (PSK) @ 250 MS/s sample rate
<b>Frequency sweep</b>	
Carrier waveform	All, From File, Arbitrary
Sweep type	All waveforms
Sweep direction	Up or Down

Sweep range (@ Max. sample rate)	
Sine wave	3.7mHz to 110 MHz
Square	3.7mHz to 62.5 MHz
Triangle	3.7mHz to 31.25 MHz
Ramp	3.7mHz to 31.25 MHz
Sweep time (@ Max. sample rate)	100ns to 4.2s
<b>General</b>	
Sample Rate Real Time	125 MS/s to 250 MS/s
Run Modes	Single, Continuous, Burst
Carrier Waveform Memory	2048 Samples / Ch.
<b>Pulse Width Modulation</b>	
Carrier waveform	Pulse
Carrier frequency	100 mHz to 20 MHz
Duty cycle modulating waveform	Sine, Triangle, Ramp, Noise, Manual
Duty cycle modulating frequency	10 $\mu$ Hz to 6.67 MHz
Source	Internal
Duty cycle deviation	0 % to 100 % of pulse period
<b>Frequency accuracy</b>	
Stability	$< \pm 5$ ppm
Aging	$< \pm 2$ ppm / year
<b>Max Interpolated Sample Rate</b>	1 GS/s (4x interpolation)
<b>Interpolation Factors</b>	1x, 2x, 4x
<b>Sampling Frequency Resolution</b>	15 digits limited by 1 nHz
<b>Amplitude, 50 <math>\Omega</math> Load (1 KHz)</b>	0V to +12 Vpp
<b>Amplitude, Open Circuit</b>	0V to +24Vpp
<b>Amplitude Resolution</b>	$< 1$ mV
<b>DC Accuracy, Open circuit (<math>\pm 12</math> V range)</b>	$\pm 0.25\%$ of amplitude range ( <i>within <math>\pm 10</math> <math>^{\circ}</math>C of calibration temperature <math>T=25</math> <math>^{\circ}</math>C, Humidity <math>\leq 80\%</math>) <math>\pm 0.3\%</math> of amplitude range (0 to 50<math>^{\circ}</math>C)</i>
<b>DC Accuracy, 50 <math>\Omega</math> Load (<math>\pm 6</math> V range)</b>	$\pm 0.25\%$ of amplitude range ( <i>within <math>\pm 10</math> <math>^{\circ}</math>C of calibration temperature <math>T=25</math> <math>^{\circ}</math>C, Humidity <math>\leq 80\%</math>) <math>\pm 0.3\%</math> of amplitude range (0 to 50<math>^{\circ}</math>C)</i>
<b>AC Accuracy, Open circuit (0 Vpp to +24 Vpp range, 1 KHz sine wave)</b>	$\pm 0.25\%$ of amplitude range ( <i>within <math>\pm 10</math> <math>^{\circ}</math>C of calibration temperature <math>T=25</math> <math>^{\circ}</math>C, Humidity <math>\leq 80\%</math>) <math>\pm 0.3\%</math> of amplitude range (0 to 50<math>^{\circ}</math>C)</i>
<b>AC Accuracy, 50 <math>\Omega</math> Load (0 Vpp to +12 Vpp range, 1 KHz sine wave)</b>	$\pm 0.25\%$ of amplitude range ( <i>within <math>\pm 10</math> <math>^{\circ}</math>C of calibration temperature <math>T=25</math> <math>^{\circ}</math>C, Humidity <math>\leq 80\%</math>) <math>\pm 0.3\%</math> of amplitude range (0 to 50<math>^{\circ}</math>C)</i>
<b>Output Impedance</b>	Selectable: 50 Ohm, Low or High Impedance
<b>Short Circuit Protection</b>	Signal outputs are robust against permanent shorts against floating ground
<b>CH1, CH2</b>	
Output connector	Front panel BNC
Voltage range (open circuit)	V <sub>Omin</sub> = -12V V <sub>Omax</sub> = +12V
Output impedance	50 Ohm, Low or High Impedance
I <sub>o</sub> max (one channel only loaded)	$\pm 200$ mA max per channel
I <sub>o</sub> max (all channels loaded)	$\pm 120$ mA max per channel
<b>External Clock</b>	
Input connector	Front panel BNC
Frequency range	5 MHz to 125 MHz
Min. input voltage swing	$\Delta$ V <sub>INmin</sub> $> 2$ V
Damage level	V <sub>INmax</sub> $< 5$ V V <sub>INmin</sub> $> -5$ V
<b>External Trigger Input</b>	
Input connector	Front panel BNC
Frequency range	DC to 125Mhz

Threshold level	VILmax = 0.8V, VIHmin=2V
Voltage range	-0.5V to 4V
Damage level	VINmax < 6V VINmin > -2V
Slope	Rising Edge or Falling
Trigger IN to Output Delay	<400 ns
Trigger IN to Output Jitter	±2 ns
<b>External Trigger Output</b>	
Output connector	Front panel BNC
Output level	TTL compatible into > 1 KOhm
Output impedance	50 Ohm nominal
<b>Digital I/O</b>	
Connector	50 pin high density (1.27mm) SCSI connector
Connector count	1
<b>Multi Channel Specifications</b>	
Sampling rate tuning	Programmable per channel couple (Ch1-2)
Skew between channels (all channels at the same sampling rate)	
Average, typical	< 300 ps
Standard deviation, typical	< 35 ps
Math	Sum, Difference, Multiply between the two channels (Ch1-2)
<b>General</b>	
Power supply voltage range	100 +/- 10% to 240 +/- 10% VAC
Power consumption	35 W max.
Power Frequency range	50/60 Hz +/- 5%
PC interface	USB 2.0
External dimensions	335 x 175 x 43 mm
Weight	1.8 Kg
Front panel connectors	- CH1 BNC - CH2 BNC - Trigger Input BNC - Trigger Output BNC - External clock input BNC - Digital I/O Pod A, 50 pin high density (1.27mm)
Rear panel connectors	- DC power jack - USB
<b>Minimum PC Requirements</b>	
Operative system	Microsoft Windows 2000/XP SP2/Vista/7 32Bit Editions
Processor	Pentium III processor, or equivalent
Memory	512Mbytes RAM
Hard Disk	150Mbytes available free space
Display Resolution	800x600
Ports	USB 2.0 or 1.1